

#18185 - 6x80+ Multifunction charger



Technical specifications:

Input Voltage:	AC Input: 100-240V /DC Input: 11-18V
Bluetooth:	YES
PC Communications:	USB Port for PC Control & Firmware Upgrade
Cooling System:	Built-in, one 30*30*7mm fan
Case Size:	135*112*60.9mm - Weight: 525g
External Port:	Temp Sensor, Servo/ESC Port, Brushless Motor Sensor Port, AC Input Power Port, Balance Socket, USB Port for PC
Delta Peak Detection:	NiCd: 3-15mV/cell NiMH: 3-15mV/cell
Trickle Charge:	50-300mA
Charge Voltage:	NiCd/NiMH: Delta peak detection LiPo: 4.18-4.3V/cell Lilon: 4.08-4.2V/cell LiFe: 3.58-3.7V/cell
Balance Current:	200mA/cell
Reading Voltage Range:	0.3-5.0V/cell
Battery Types/Cells:	NiCd/NiMH: 1-15cells LiPo/Lilon/LiFe: 1-6cells Pb: 2-20V
Battery Capacity Range:	NiCd/NiMH: 0.1-1.1V/cell LiPo/Lilon/LiFe: 100-50,000mAh Pb: 100-50,000mAh
Charge Current:	0.1-10.0A
Safety Timer:	1-720 minutes, Off
Charge Wattage:	AC50W, DC80W
Discharge Current:	0.1-5.0A(±10%)
Discharge Cut-off Voltage:	NiCd/NiMH: 0.1-1.1V/cell LiPo: 3.0-3.3V/cell Lilon: 2.9-3.2V/cell LiFe: 2.6-2.9V/cell Pb: 1.8V
Discharge Wattage:	8W
Balance Cells:	6 cells
Memory:	10 different charge/discharge profiles
Charge Method:	CC/CV for lithium types and lead (pb) batteries, Delta-peak Sensitivity for NiMH/NiCd.

ActionSportGames A/S

Bakkegaardsvej 304 Phone: +45 8928 1888

DK-3050 Humlebaek

Denmark

Fax:

+45 4919 3160

sales@actionsportgames.com

actionsportgames.com